

NEW RT-10 ROPE TESTER

Test the dielectric strength of your rope in the field

- · Easily test any length of rope before use
- Clear visual and audible indication of contaminated sections
- Powered by field-replaceable 9V batteries





SPECIFICATIONS

| Output Voltage/Current | 9kVDC/ 60μA Max |
|--|--------------------------|
| Current Threshold for "Bad Rope" Indication | 15 µA |
| Battery Type | (2) 9V Field-Replaceable |
| Battery Life | 8 Hours of Typical Use |
| Operating Temperature Range | 0°F to 125°F |
| Dimensions | 7.7" x 4.0" x 3.7" |

ORDERING INFORMATION

| CAT. NO. | DESCRIPTION |
|----------|--|
| RT-10 | Rope Tester includes carrying case, (2) 9V Batteries |



Check out these additional HDE Products

PRX™ Proximity Voltage Detector



Easily verify the presence of voltage without contacting the conductor. Three models available to detect voltages from 120V up to 500kV

V-Watch® Personal Voltage Detector



Provides another level of safety for line crews, storm restoration workers and first responders by alerting them to the presence of electric fields or energized equipment

Double Vision® Meters





DDVIP-138

Voltmeters and Voltage indicator with available wireless phasing capabilities featuring a patented synchronized dual-display design.

For more information, visit our website at **Greenlee.com/HDE**

