Seasense Marine/Sports Horn

Safety Data Sheet

According to Federal Register Rules and Regulations Revision date: 03/21/2017 :

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1.	Product identifier	
Product f	orm	: Substance
Trade na	me	: Seasense Marine/Sports Horn
Model Nu	umbers	: 50074008,50074035, 50074041, 50074080
CAS No		: 75-37-6
Formula		: C2H2F4
1.2.	Relevant identified uses of the subst	ance or mixture and uses advised against
Use of th	e substance/mixture	: Aerosol Horn
1.3.	Details of the supplier of the safety d	lata sheet
Unified N	larine Inc.	
4488 112th Street		
Urbandale, IA 50322		
T 800-282-8725		
1.4.	Emergency telephone number	
Emergen	cy number	: 800-282-8725

SECTION 2: Hazards identification

GHS Categories

Criteria		Category	Signal Word	Pictograms
Gas Under Pressure	Liquefied Gas	3	Warning	Gas Cylinder

Note: Non-flammable Aerosol. Not defined as flammable aerosol because heat of combustion is <20 kJ/g, ignition distance <15 cm, and it passes enclosed space ignition test according to 16 CFR 1500.3(c)(6) for the U.S. Federal Hazard Substance Act of the Consumer Product Safety Commission regulations. Not defined as a flammable aerosol under the Canadian Controlled Product Regulation SOR/88-66, 40 Division 5 criteria.

Label Elements

Signal Word	WARNING
Pictograms Hazard Statements	
	H280: Contains gas under pressure; may explode if heated
Prevention	Precautionary Statements
P251	Do not pierce or burn, even after use.
Storage	Precautionary Statements
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].

Hazards Not Otherwise Classified

HCS2012 Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Simple Asphyxiant	May displace oxygen and cause rapid suffocation.	Warning	Not applicable
Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Frostbite	Skin contact with liquid or aerosol jet may lead to frostbite	Warning	Not applicable
Specific flammability	Liquid form is flammable. (Liquid form can be ejected if the aerosol can is not held upright during use.)	Warning	Not applicable
Intentional Overexposure	Intentional misuse and inhalation abuse may cause cardiac or central nervous systems effects.	Warning	Not applicable
	May form explosive gas mixture with air.	Warning	Not applicable

SECTION 3: Composition/information on

Name : 1,1-Difluoroethane, liquefied, under pressure	
CAS No : 75-37-6	
EC no : 200-866-1	

Name	Product identifier	%	Classification (GHS-US)
1,1-Difluoroethane, liquefied, under pressure (Main constituent)	(CAS No)75-37-6	> 99	Liquefied gas, H280

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measure	es
First-aid measures general	 Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with labored breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give alcohol to drink.
First-aid measures after inhalation	: Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.
First-aid measures after skin contact	: Rinse with water. In case of frostbites: Wash immediately with lots of water (15 minutes)/shower. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital.
First-aid measures after eye contact	: Rinse with water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.
First-aid measures after ingestion	: Not applicable.
4.2. Most important symptoms and	effects, both acute and delayed
Symptoms/injuries	: Contains refrigerated gas; may cause cryogenic burns or injury. Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/injuries after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Dizziness. Slight irritation. Headache. Nausea. Vomiting. Coordination disorders. Disturbances of consciousness. Disturbances of heart rate.
Symptoms/injuries after skin contact	: Frostbites.
Symptoms/injuries after eye contact	: No data available.
Symptoms/injuries after ingestion	: Not applicable.
Chronic symptoms	: No effects known.
4.3. Indication of any immediate me	edical attention and special treatment needed
No additional information available	
SECTION 5: Firefighting measur	es
5.1. Extinguishing media	
Cuitable outinguishing media	Water aprov. BC powder, Carbon diavide

Suitable extinguishing media	: Water spray. BC powder. Carbon dioxide.
Unsuitable extinguishing media	: No unsuitable extinguishing media known.
5.2. Special hazards arisin	g from the substance or mixture
Fire hazard	: DIRECT FIRE HAZARD. Flammable aerosol. Gas/vapor flammable with air within explosion limits. INDIRECT FIRE HAZARD. May build up electrostatic charges: risk of ignition. May be ignited by sparks. Gas/vapor spreads at floor level: ignition hazard.
Explosion hazard	: DIRECT EXPLOSION HAZARD. Gas/vapor explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD. Heat may cause pressure rise in tanks/drums: explosion risk. may be ignited by sparks.
Reactivity	: On heating/burning: release of toxic and corrosive gases/vapor e.g.: hydrofluoric acid, carbonylfluoride. Reacts violently with (strong) oxidizers.
5.3. Advice for firefighters	
Firefighting instructions	If no hazard for/from the surroundings: controlled burning. If hazardous substances are nearby: consider extinguishment. Extinguish only if gas supply/leak can be shut afterwards. Cool tanks/drums with water spray/remove them into safety. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Dilute toxic gases with water spray.
Protection during firefighting	: Heat/fire exposure: compressed air/oxygen apparatus.
Other information	: NFPA Aerosol Level 1.

6.1.		equipment and emergency procedures
General	measures	: Remove ignition sources. Use special care to avoid static electric charges. Eliminate every possible source of ignition. No naked lights. No smoking.
6.1.1.	For non-emergency personnel	
Protectiv	ve equipment	: Insulating gloves. Protective goggles. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus. See "Material-Handling" to select protective clothing.
Emerge	ncy procedures	: Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Avoid ingress of water in the containers. Wash contaminated clothes.
6.1.2.	For emergency responders	
Protectiv	ve equipment	: Equip cleanup crew with proper protection.
Emerge	ncy procedures	: Ventilate area.
6.2.	Environmental precautions	
Prevent	spreading in sewers.	
6.3.	Methods and material for contain	ment and cleaning up
For con	tainment	: Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the liquid spill. Tip the containe on one side to stop the leakage. Try to reduce evaporation. Measure the concentration of the explosive gas-air mixture. Dilute/disperse combustible gas/vapor with water curtain. Provide equipment/receptacles with earthing. Do not spray water on unheated tank walls. Do not use compressed air for pumping over spills.
Methods	s for cleaning up	: Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. See "Material-handling" for suitable container materials. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.
6.4.	Reference to other sections	
See Hea	ading 8. Exposure controls and person	al protection.
SECT	ON 7: Handling and storage	
71	Precautions for safe handling	

7.1. Precautions for safe handling	
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use.
Precautions for safe handling	: Comply with the legal requirements. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not use compressed air for pumping over. Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe normal hygiene standards. Measure the concentration in the air regularly. Measure the oxygen concentration in the air. Work under local exhaust/ventilation.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
7.2. Conditions for safe storage, in	ncluding any incompatibilities
Technical measures	: Level 1 Aerosol.
	Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.
Storage temperature	: < 50 °C
Heat of Combustion	: -7,950 Btu/lb = -4,420 cal/g = -185X10+5 J/kg
Heat-ignition	: KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.
Prohibitions on mixed storage	: KEEP SUBSTANCE AWAY FROM: oxidizing agents.
Storage area	: Ventilation at floor level. Fireproof storeroom. Provide for a tub to collect spills. Provide the tank with earthing. Keep out of direct sunlight. Meet the legal requirements.
Special rules on packaging	: SPECIAL REQUIREMENTS: with pressure relief valve. clean. correctly labelled. meet the legal requirements.
Packaging materials	: SUITABLE MATERIAL: steel. stainless steel. monel steel. lead. aluminium. copper. tin.
7.3. Specific end use(s)	

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls	
Appropriate engineering control	: Local exhaust ventilation, vent hoods.
Personal protective equipment	: Avoid all unnecessary exposure. Gloves. Safety glasses.
Materials for protective clothing	: GIVE GOOD RESISTANCE: butyl rubber. leather. neoprene. polyethylene. PVC.
Hand protection	: Insulated gloves.
Eye protection	: Safety glasses.
Skin and body protection	: Protective clothing.
Respiratory protection	: High vapor/gas concentration: self-contained respirator. Maintain oxygen levels above 19.5% in the workplace. Use supplied air respiratory protection if oxygen levels are below 19.5% or durin emergency response to a release of this product.Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.
SECTION 9: Physical an	d chemical properties
	physical and chemical properties
Physical state	: Gas
Annearance	

: Gas
:
Liquefied gas. : 66.05 g/mol : Colorless.
Mild odor. Slight Ether-like odor : No data available
:
No data available
No data available
:
-117 °C :
No data available
: -25 °C
:
< -50 °C :
114 °C
: 455 °C
:
No data available :
No data available
5100 hPa :

	11700 hPa
Critical pressure	: 44960 hPa
Relative vapor density at 20 °C	2.3
Relative density	
	1.0 (-25 °C)
Specific gravity / density	
	1004 kg/m³ (-25 °C)
Solubility	Poorly soluble in water. Soluble in organic solvents. Water:
	0.54 g/100ml (0 °C)
Log Pow	
	0.75 (Experimental value)
Log Kow	
	No data available
Viscosity, kinematic	
	No data available
Viscosity, dynamic	No data available
viscosity, dynamic	
	0.37 Pa.s (-31 °C)
Explosive properties	
	No data available
Oxidizing properties	
	No data available
Explosive limits	
	4 - 19 vol %
	112 - 518 g/m³
9.2. Other information	
VOC content	0%

VOC content	: 0%
Gas group	: Liquefied gas
Other properties	: Gas/vapor heavier than air at 20°C. May generate electrostatic charges.

SECTION 10: Stability and reactivity

10.1. Reactivity

On heating/burning: release of toxic and corrosive gases/vapor e.g.: hydrofluoric acid, carbonylfluoride. Reacts violently with (strong) oxidizers.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

: Not classified

176 mg/l/4h (Rat; Literature study)

R152A (\f)75-37-6

LC50 inhalation rat (mg/l) LC50 inhalation rat (ppm)

> 437500 ppm/4h Mortality in 2/6 at 43.75% and 1/6 at 38.3%. At \geq 17.52% lethargy, laboured breathing, reduced responsiveness to sound were observed. At 6.64% only hyperaemia and shallow breathing were observed.

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified. Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified. Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated	: Not classified. Based on available data, the classification criteria are not met
exposure)	
Aspiration hazard	: Not classified. Based on available data, the classification criteria are not met
Potential Adverse human health effects and	: Based on available data, the classification criteria are not met.
symptoms	
Symptoms/injuries after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Dizziness. Slight irritation. Headache. Nausea. Vomiting. Coordination disorders. Disturbances of consciousness. Disturbances of heart rate.
Symptoms/injuries after skin contact	: Frostbites.
Symptoms/injuries after eye contact	: No data available.
Symptoms/injuries after ingestion	: Not applicable.
	: No effects known.
Chronic symptoms SECTION 12: Ecological information	
SECTION 12. Ecological information	
12.1. Toxicity	
Ecology - air	:Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009). Included in the list of substances which may contribute to the greenhouse effect (Regulation (EC) No 842/2006). TA-LuftKlasse 5.2.5.
Ecology - water	:Mild water pollutant (surface water). No data available on ecotoxicity.
12.2. Persistence and degradability	
,	
12.2. Persistence and degradability R152A (75-37-6)	
,	Biodegradability in water: no data available.
R152A (75-37-6)	Biodegradability in water: no data available.
R152A (75-37-6)	Biodegradability in water: no data available.
R152A (75-37-6)	Biodegradability in water: no data available.
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential	Biodegradability in water: no data available.
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6)	
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow	0.75 (Experimental value)
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6)	
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow	0.75 (Experimental value)
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow	0.75 (Experimental value)
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow Bioaccumulative potential	0.75 (Experimental value)
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow Bioaccumulative potential 12.4. Mobility in soil No additional information available	0.75 (Experimental value)
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow Bioaccumulative potential 12.4. Mobility in soil No additional information available 12.5. Other adverse effects	0.75 (Experimental value) Low potential for bioaccumulation (Log Kow< 4).
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow Bioaccumulative potential 12.4. Mobility in soil No additional information available	0.75 (Experimental value)
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow Bioaccumulative potential 12.4. Mobility in soil No additional information available 12.5. Other adverse effects	0.75 (Experimental value) Low potential for bioaccumulation (Log Kow< 4). : Avoid release to the environment.
 R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow Bioaccumulative potential 12.4. Mobility in soil No additional information available 12.5. Other adverse effects Other information SECTION 13: Disposal consideration 	0.75 (Experimental value) Low potential for bioaccumulation (Log Kow< 4). : Avoid release to the environment.
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow Bioaccumulative potential 12.4. Mobility in soil No additional information available 12.5. Other adverse effects Other information SECTION 13: Disposal consideratio 13.1. Waste treatment methods	0.75 (Experimental value) Low potential for bioaccumulation (Log Kow< 4). : Avoid release to the environment.
 R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow Bioaccumulative potential 12.4. Mobility in soil No additional information available 12.5. Other adverse effects Other information SECTION 13: Disposal consideration 	 0.75 (Experimental value) Low potential for bioaccumulation (Log Kow< 4). : Avoid release to the environment. ns : Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Refer to manufacturer/supplier for information on recovery/
 R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow Bioaccumulative potential 12.4. Mobility in soil No additional information available 12.5. Other adverse effects Other information SECTION 13: Disposal consideratio 13.1. Waste treatment methods Waste disposal recommendations 	 0.75 (Experimental value) Low potential for bioaccumulation (Log Kow< 4). : Avoid release to the environment. 15 : Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Refer to manufacturer/supplier for information on recovery/ recycling.
R152A (75-37-6) Persistence and degradability 12.3. Bioaccumulative potential R152A (75-37-6) Log Pow Bioaccumulative potential 12.4. Mobility in soil No additional information available 12.5. Other adverse effects Other information SECTION 13: Disposal consideratio 13.1. Waste treatment methods	 0.75 (Experimental value) Low potential for bioaccumulation (Log Kow< 4). : Avoid release to the environment. ns : Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Refer to manufacturer/supplier for information on recovery/

SECTION 14: Transport information In accordance with ADR / RID / IMDG / IATA / ADN

In accordance with ADr	
US DOT (ground):	UN1030, 1,1-Difluoroethane, 2.1, Level 1 Aerosol
ICAO/IATA (air): IMO/IMDG (water):	UN1950, Aerosols, Flammable, 2.1, Limited Quantity UN1950, Aerosols, Flammable, 2.1, Limited Quantity
Special Provisions:	DOT-SP 11516: In accordance with this special permit, this product is not subject to labeling requirements unless offered for transportation by air. This product is not subject to placarding requirements. Outside packaging must be marked with proper shipping description and 'DOT-SP 11516'

14.2. UN proper shipping name

DOT Proper Shipping Name	: 1,1-Difluoroethane
DOT Special Provisions (49 CFR 172.102)	: DOT-SP 11516: In accordance with this special permit, this product is not subject to labeling requirements unless offered for transportation by air. This product is not subject to placarding requirements. Outside packaging must be marked with proper shipping description and 'DOT-SP 11516'
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
14.3. Additional information	
Other information	: No supplementary information available.
Special transport precautions	: DOT-SP 11516: In accordance with this special permit, this product is not subject to labeling requirements unless offered for transportation by air. This product is not subject to placarding requirements. Outside packaging must be marked with proper shipping description and 'DOT-SP 11516'.
Overland transport	
Class (ADR)	: 2 - Gases
Hazard identification number (Kemler No.)	: 23
Classification code (ADR)	: 2F
Additional Information:	TDG Canada: AVW, Inc has been granted Equivelancy Certificate SU 9211 (ren. 1) by the TCSS, TDGD to offer for transportby road, rail and marine.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : Forbidden (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 150 kg CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations		
R152A (75-37-6)		
SARA Section 311/312 Hazard Classes	Fire hazard Sudden release of pressure hazard Immediate (acute) health hazard	
15.2. International regulations		
CANADA		
R152A (75-37-6)		
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Aerosol	

 NEW ZEALAND

 HSNO regulation
 Hazard Class: 2.1.2A

 UN1030, 1,1-Difluoroethane, R152A Flammable, Gases that are not otherwise hazardous

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Gas 1 H220 Press. Gas

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD] F+;

R12

Full text of R-phrases: see section 16

15.2.2. National regulations

No additional information available

15.3. US State regulations

R152A (75-37-6)

State or local regulations

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

SECTION 16: Other information

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.