

SERIES 1

FULL-BODY HARNESS

TECHNICAL DATA & SELL SHEET - ISSUE 1





Webbing: Polyester Buckles: Galvanized Steel

D-Rings: Galvanized Steel Capacity: 130-420 Lbs

MULTIPLE BUCKLE CONFIGURATIONS AVAILABLE

FOR MORE INFO, PLEASE CALL ${f 1.800.466.6385}$ OR VISIT ${f GUARDIANFALL.COM}$





SERIES 1

FULL-BODY HARNESS

TECHNICAL DATA & SELL SHEET - ISSUE 1

Applications



Personal Fall Arrest: A Series 1 Harness may be used in Personal Fall Arrest applications as a component of a Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', unless used in combination with equipment explicitly certified for extended free fall. Applicable D-ring: Dorsal.



Restraint: A Series 1 Harness may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, & Shoulder.



Work Positioning: A Series 1 Harness, configured with side D-rings, may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side.



Rescue/Confined Space: A Series 1
Harness may be used in Rescue/Confined
Space applications. Rescue systems
function to safely recover a worker from
a confined location or after exposed to
a fall. There are various configurations
of Rescue systems depending on the
type of rescue. Structure must withstand
loads applied in the directions permitted
by the system of at least 3,000 lbs.
No free fall is permitted. Applicable
D-rings: Dorsal, Chest, & Shoulder.

Standards

• OSHA 1910 • OSHA 1926 Subpart M • ANSI Z359.11-2014 • ANSI A10.32-2012 regulations



Made from some or all of the following materials: polyester and galvanized steel..

Always follow all manufacturer's instructions for proper adornment and use. Some steps of adorning a harness may require assistance from another person.

Upon completely adorning a harness, Guardian Fall Protection recommends that another person, with knowledge of the safe and correct use of the harness, inspect to ensure the harness is being worn correctly.

FOR MORE INFO, PLEASE CALL 1.800.466.6385 OR VISIT GUARDIANFALL.COM





SERIES 1

FULL-BODY HARNESS

INDIVIDUAL PRODUCT CODES



Prod. Code	Description	Size	User Weight
37000	Chest & Leg Pass-Through Buckles	XS-S	130-420 lbs
37001	Chest & Leg Pass-Through Buckles	M-L	130-420 lbs
37002	Chest & Leg Pass-Through Buckles	XL-2XL	130-420 lbs
37004	Chest Pass-Through, Leg Tongue Buckles	XS-S	130-420 lbs
37005	Chest Pass-Through, Leg Tongue Buckles	M-L	130-420 lbs
37006	Chest Pass-Through, Leg Tongue Buckles	XL-2XL	130-420 lbs
37008	Chest & Leg Pass-Through Buckles with Side D-rings	XS-S	130-420 lbs
37009	Chest & Leg Pass-Through Buckles with Side D-rings	M-L	130-420 lbs
37010	Chest & Leg Pass-Through Buckles with Side D-rings	XL-2XL	130-420 lbs
37012	Chest Pass-Through, Leg Tongue Buckles with Side D-rings	XS-S	130-420 lbs
37013	Chest Pass-Through, Leg Tongue Buckles with Side D-rings	M-L	130-420 lbs
37014	Chest Pass-Through, Leg Tongue Buckles with Side D-rings	XL-2XL	130-420 lbs
37016	Chest Quick-Connect, Leg Tongue Buckles	XS-S	130-420 lbs
37017	Chest Quick-Connect, Leg Tongue Buckles	M-L	130-420 lbs
37018	Chest Quick-Connect, Leg Tongue Buckles	XL-2XL	130-420 lbs
37020	Chest Quick-Connect, Leg Tongue Buckles with Side D-rings	XS-S	130-420 lbs
37021	Chest Quick-Connect, Leg Tongue Buckles with Side D-rings	M-L	130-420 lbs
37022	Chest Quick-Connect, Leg Tongue Buckles with Side D-rings	XL-2XL	130-420 lbs

Custom configurations available. Not repairable.
Contact customer service
for details.

FOR MORE INFO, PLEASE CALL 1.800.466.6385 OR VISIT GUARDIANFALL.COM

